ATX 27.5 2

ON-ROAD OR OFF-ROAD, THE CHOICE IS YOURS. WITH SMOOTH, CONFIDENT 27.5 WHEELS, THIS IS YOUR INVITATION TO EXPLORE.



SPECIFICATIONS

FRAME	
SIZES	XXS,XS,S,M,L,XL
COLORS	Black/Red;Black/Blue;Yellow
FRAME	ALUXX-Grade Butted Aluminum
FORK	SR Suntour XCT 27.5" , 100mm Travel,
COMPONENTS	
HANDLEBAR	Low Rise, 31.8mm
STEM	Giant Sport Alloy, 15 degree rise
SEATPOST	Giant Sport 30.9
SADDLE	Giant Connect
PEDALS	One-piece black PP, 9/16"
DRIVETRAIN	
SHIFTERS	Shimano EF40, 3x7 Speed
FRONT DERAILLEUR	Shimano Tourney
REAR DERAILLEUR	Shimano Tourney
BRAKES	Tektro M280 [F]160mm [R]160mm
BRAKE LEVERS	Shimano EF41
CASSETTE	Shimano TZ31 14-34, 7s
CHAIN	KMC Z51, 7s
CRANKSET	SR Suntour XCT-T318, 28/38/48
BOTTOM BRACKET	SR Suntour Cartridge BB
WHEELS	
RIMS	CR70 27.5X32H
HUBS	Joytech disc hubs, alloy hub, double-sealed, cassette style, loose ball bearing, 32H
SPOKES	Stainless 14G
TIRES	Giant Sport, 27.5X2.1

FRAME DESIGN

At the core of this entry-level go-anywhere bike is a lightweight ALUXX frameset designed to handle the specific geometry demands of 27.5-inch wheels. A smart mix of weight, comfort and affordability are built into each frame, offering the recreational and adventure rider the first all terrian X-road bike.

- ALUXX-grade, butted aluminum tubeset
- Quick handling, 27.5-inch wheel, optimized geometry for nimble hardtail riding characteristics

ALUXX Aluminum Technology 27.5

FEATURES

- SR Suntour XCT 27.5" lockout
- Shimano Tourney 21-speed drivetrain
- Tektro M280 brakes
- Giant CR70 aluminium double-wall rims
- Color: black/red, black/blue, yellow

GEOMETRY

Size	Part number	Head Angle	Seat Angle	Top Tube	Reach	Head Tube	Stack	Chain Stay	Wheel Base	Standover Height
Inches		Degree	Degree	Centim..	Centim..	Centim..	Centim..	Centim..	Centim..	Centim..
XXS/13	N/A	70.0	74.0	53.0	N/A	9.5	N/A	43.5	103.8	67.8
XS/14.5	N/A	70.5	73.0	55.1	N/A	10.9	N/A	43.5	104.9	70.9
S/16	N/A	70.5	73.0	56.9	N/A	11.4	N/A	43.5	105.9	73.4
M/18	N/A	70.5	73.0	58.9	N/A	12.7	N/A	43.5	108.0	77.2
L/20	N/A	70.5	72.5	61.0	N/A	13.2	N/A	43.5	109.2	80.8
XL/22	N/A	69.5	73.0	64.0	N/A	14.0	N/A	43.5	113.4	84.1